


METZNER MBS


The series machine with over 10,000 possible combinations



FASTER AND MORE PWOERFUL: EXCENTER



- Up to 400 cuts per minute in the start-stop-mode
- Exact right cutting angles due to the stop before each cut
- Up to 800 cuts per minute in the continuous mode
- Electric drive, hence very quiet





ALL TECHNICAL DETAILS AT A GLANCE

Performance data	MBS 100	MBS 200	MBS 400
Dimension of material: width max.	90 mm	190 mm	390 mm
Dimension of material: height max.	30 mm 80 mm		
Length interval	0.1 mm		
Typical repeat accuracy	± (1mm + 0.2 % l)		
Feeding speed max.	60 MPM 150 MPM 60 MPM 120 MPM		
Cutting performance	170 cuts/min.	130 cuts/min.	60 cuts/min.
Available cutting technologies	MBS 100	MBS 200	MBS 400
Die cutting	√	\checkmark	√
Shear cutting	\checkmark	\checkmark	\checkmark
Draw cutting	\checkmark	_	_
Blade cutting	\checkmark	\checkmark	\checkmark
Hot cutting	√	\checkmark	_
Rotary cutting	\checkmark	\checkmark	\checkmark
Tools cutting	\checkmark	\checkmark	_
Drilling	\checkmark	\checkmark	\checkmark
Technical data	MBS 100	MBS 200	MBS 400
Dimensions (L x W x H)	depending on equipment		
Electrical connection	230 V 50/60 Hz 10 A		
Compressed air connection	6 bar		
Weight	depending on equipment		
Drive	Schneider Siemens		
Display	5,7" touch screen (color) 7" touch screen (color)		
Consumption kVA bar	P: 1.0 kVA approx. 120 l/min. P: 1.0 kVA approx. 240 l/min		
Noise (idle)	< 75dB (A)		