

# KRI 850 C (Coil)

FOR QUICK AND EFFICIENT CABLE COILING



## FEATURES

- Suitable even for short cable lengths starting at 2.5 m
- Small and compact cable coils for cable diameters up to 35 mm

For the CBP-Version the operating mode depends on the dimensions and weight of the cable coil and the breaking load of the rubber cord.

## TECHNICAL DATA

Performance	KRI 850 C	KRI 850 CB	KRI 850 CBP
Coil inner diameter Manual mode Automatic mode	min. 250 mm / max. 600 mm	min. 250 mm / max. 600 mm	min. 250 mm / max. 600 mm in Auto-Mode max. 400 mm
Coil outer diameter Manual mode Automatic mode	max. 850 mm (760 mm with pins)	max. 850 mm (760 mm with pins)	max. 850 mm (760 mm with pins) in Auto-Mode max. 600 mm
Coil height	max. 160 mm	max. 160 mm	max. 160 mm
Cable diameter (flexible cable)	max. 35 mm	max. 35 mm	approx. 6 mm - 35 mm
Coil weight	approx. 80 kg	approx. 80 kg	approx. 20 kg
Control system	PLC and LCD operator Terminal		
Interfaces	Synchronization with several types of prefeeding systems and cable processing machines		
Speed	Coiling speed synchronized with cable processing machine		
Power supply	230 VAC / 10 AT	230 VAC / 10 AT	230 VAC / 10 AT
Pneumatic	6 bar	6 bar	6 bar
Revolution	max. 133 min.-1	max. 133 min.-1	max. 133 min.-1
Weight	approx. 250 kg	approx. 350 kg	approx. 550 kg
Dimension (L x W x H)	990 x 1163 x 1333 mm	1806 x 1163 x 1333 mm	2778 x 1163 x 2020 mm

LOCATION SWITZERLAND

**Ramatech Systems AG** . Hohenrainstrasse 36 . CH - 6280 Hochdorf  
Phone: +41 41 914 26 26 . E-Mail: info@ramatech.ch

LOCATION GERMANY

**Ramatech Systems GmbH**. Messerschmittstraße 30 . D - 89231 Neu-Ulm  
Phone: +49 731 40 199 200 . E-Mail: info@ramatech.de