

METZNER AM 3800 / AM 3850













For powerful and versatile cable processing



FEATURES

- Automatic cutting to length
- Multi-stage stripping (AM 3850 also of coaxial cables)
- „Double knife cutting system“ for more output
- User friendly software with touch screen
- Cable diameter up to 20 mm

PROCESS OVERVIEW AM 3800 AND AM 3850

	Cutting of cables and strands		Jacket stripping of multi conductor cables
	Stripping with partial and full pull-off		Incise cutting and length slitting
	Window stripping		Metal braid stripping with protection cap
	Extremely long pull-offs in multiple stages		Multi-step stripping
	Cutting and stripping of teflon cables		Wire processing
	Printing and marking		Multi-step processing of coaxial cables (AM 3850 only)



ALL TECHNICAL DETAILS AT A GLANCE

Performance data	AM 3800	AM 3850
Wire size range stranded/solid	70 mm ²	
Cable diameter max.	20 mm	
Length interval	0.1 mm	
Typical repeat accuracy	± (1mm + 0.2 % l)	
Feeding speed max.	590 ft/min	
Stripping length max. Cable start Cable end	0-200 mm 0-145 mm	0-200 mm 0-145 mm
Cable length min. max.	70 mm 999 mm	
Wire stripping force	250 N	
Equipment	AM 3800	AM 3850
Cutting system	knife	knife and rotary unit
Feeding system	belt	
Cutting	✓	✓
Stripping with full pull-off	✓	✓
Stripping with partial pull-off	✓	✓
Slitting	✓	✓
Multistage stripping	3 stages on each side	
Ribbon cable	–	–
BOM processing	✓	✓
Material end recognition	✓	✓
Cable length compensation	✓	✓
Recipe data management	✓	✓
Length measuring system	option	option
Printing interface	option	option
Interface for peripherals	option	option
IT network interface	option	option
Rotary cutting unit	–	✓
Length slitting unit	option	option
Networking / MES interface (Industry 4.0)	option	option
Remote servicing	PC integrated	PC integrated
USB/Ethernet	✓	✓
Blades	V blade, Radius V blade, Slitting blade	V blade, Radius V blade, Slitting blade, Rotary blade
Number of pairs of blades in use	2	2
Technical data	AM 3800	AM 3850
Dimensions (L x W x H)	691 mm x 788 mm x 926 mm	928 mm x 788 mm x 926 mm
Electrical connection	230 V 50 Hz	
Compressed air connection	6 bar	
Weight	130 kg	160 kg
Drive	SPS / PC	
Display	15" touch screen	
Consumption kVA bar	P: 0.8 kVA approx. 50 l/min.	
Noise (idle)	< 75dB (A)	